

Digital Application Sheet



VEHICLE MANUFACTURER	FORD
MODEL	MK6 TRANSIT RWD
YEAR OF MANUFACTURE	2000—2006
ENGINE TYPE	ALL
TRANSMISSION	MAN. 5-SPEED
VOLTAGE	12V



STONERIDGE DIGITAL KIT FOR THIS VEHICLE: 7800-099


PARTS LIST	QUANTITY	STONERIDGE PART NO.
SE5000 TACHOGRAPH	1	
APPLICATION SHEET	1	6800-319
SENDER	1	
SENDER CABLE	1	
SHROUD SEALING KIT	1	
DRIVER QUICKGUIDE	1	102022P/01
INSTALLATION KIT	1	
TACHO MOTION GPS	1	

To configure the SE5000 KRM using the SE5000CS, select the Transit 2005-ON icon within the Ford manufacturer type.

Ensure that 2nd Source of motion is set to C3 Enabled and C3 Speed Factor is set correctly within Sensor Test within MKIII Programmer on the Optimo.

ADDITIONAL VEHICLE MANUFACTURERS PARTS REQUIRED	VEHICLE MANUFACTURERS PART NO.
FORD POD FOR MOUNTING TO TOP OF DASH. (FOUR PARTS)	4048128
	1012907
	4111359
	4125383

FITTING INFORMATION



Tachograph (4)

MT82-SIDE VIEW

TO THE LEFT IS A DIAGRAM SHOWING THE POSITION TO FIT THE SENDER UNIT.

CHECK GEARBOX FOR CORRECT SENDER LENGTH

SENDER 9954-250

L=19.8mm WITH 1.2mm WASHER

Workshop Technical Support

Tel +44 (0) 1382 866 400 (choose opt.2. opt.1)

Fax +44 (0) 1382 866 401

Sales Office

Tel +44 (0) 1382 866 400 (choose opt.1)

Fax +44 (0) 1382 866 401



Whilst we have endeavoured to ensure the accuracy of the information supplied, Stoneridge Electronics cannot be held responsible for any errors or omissions. It is the installer's responsibility to ensure compliance with specific vehicle manufacturers repair procedures, especially with regard to the procedure for disconnection/reconnection of the battery. Failure to comply with the vehicle manufacturers instructions may result in personal injury and/or component damage/data loss.



1. The 2nd Source of motion is obtained by using the GPS Module and cable harness as shown.
2. The cable harness is connected directly inline with the tachograph power cable when connecting to the tachograph as shown.
3. The GPS Module should be placed in a suitable area within the cab, preferably in an area next to the windscreen.

Workshop Technical Support

Tel +44 (0) 1382 866 400 (choose opt.2. opt.1)

Fax +44 (0) 1382 866 401

Sales Office

Tel +44 (0) 1382 866 400 (choose opt.1)

Fax +44 (0) 1382 866 401



Whilst we have endeavoured to ensure the accuracy of the information supplied, Stoneridge Electronics cannot be held responsible for any errors or omissions. It is the installer's responsibility to ensure compliance with specific vehicle manufacturers repair procedures, especially with regard to the procedure for disconnection/reconnection of the battery. Failure to comply with the vehicle manufacturers instructions may result in personal injury and/or component damage/data loss.

SE5000 Programming Sheet



PROGRAMMING PARAMETERS FOR FITTING THIS VEHICLE WITH AN SE5000 KRM SERIES TACHOGRAPH.

Note. Read the parameters of the tachograph to be replaced, and note all connections to the tachograph, paying particular attention to Vpulse, dual axle configuration, D8 serial data, Revs input etc.

The below vehicle settings are the default vehicle settings which should be applied. However, individual vehicle specifications may vary.

Default setting for D6 outputs that can be switched between ISO & Open collector (o/c) is ISO.

The vehicle must be calibrated in an approved manner after fitting.

The road speed limiter must be calibrated after a replacement tachograph is fitted.

The illumination of the KRM series tachograph can be changed between White & Green, please select the colour best suited to the vehicle illumination.

If you are in doubt regarding the replacement of any tachograph with a KRM series product please call:-

TACHOGRAPH	CANBUS	CAN	CAN	ILLUMINATION	REVS INPUT	SPEED LIMITER	D6
5002KRM	OFF	N/A	N/A	A2	C3	90km/H	ISO

READ ALL DATA LOG

PARAMETER	VALUE / SETTING	PARAMETER	VALUE / SETTING
W-FACTOR		Def. KEY ON/OFF	
K-FACTOR		RPM FACTOR	
L-FACTOR		D4 PIN FUNCTION	
TYRE SIZE		D5 PIN FUNCTION	
VIN		D6 PIN FUNCTION	
VRN		D7 PIN FUNCTION	
VEH. REG. NATION		SERIAL DATA OUT (D8)	
PREF. LANGUAGE		C1 PIN FUNCTION	
CURRENT TIME		FILTER PIN B3	
CURRENT DATE		CAN TRIP RESET	
TIME OFFSET		CAN WAKE UP	
NEXT CALIB.DATE		RD CAN CONFIG	
INSTALL DATE		ADD. EVENT REC.	
ACTIVATION TIME	READ ONLY. --DATE FORMAT / UNACTIVATED	ENG. SPEED REC.	
SERVICE DELAY		VRES D	
ODOMETER		VEH. SPEED REC.	
O/P SHAFT FACTOR		VRVSD	
SPEEDO OP FACTOR		PRE-OVERSPEED	
RESET HEARTBEAT		PRE-NEXT CALIBRATION	
LOW SPEED LIMIT		WARRANTY TIME	
BACKLIGHT SELECT		LOW POWER BAND	
ILLUMINATION LEVEL		ECONOMY POWER BAND	
ILLUMINATION OFF		POOR ECONOMY	

Workshop Technical Support

Tel +44 (0) 1382 866 400 (choose opt.2. opt.1)

Fax +44 (0) 1382 866 401

Sales Office

Tel +44 (0) 1382 866 400 (choose opt.1)

Fax +44 (0) 1382 866 401



Whilst we have endeavoured to ensure the accuracy of the information supplied, Stoneridge Electronics cannot be held responsible for any errors or omissions. It is the installer's responsibility to ensure compliance with specific vehicle manufacturers repair procedures, especially with regard to the procedure for disconnection/reconnection of the battery. Failure to comply with the vehicle manufacturers instructions may result in personal injury and/or component damage/data loss.