

STONERIDGE DIGITAL KIT 7800-197



VEHICLE MANUFACTURER	LAND ROVER
MODEL	DISCOVERY 5
YEAR OF MANUFACTURE	2017 ON
ENGINE TYPE	ALL
TRANSMISSION	ALL
VOLTAGE	12V




PARTS LIST

QUANTITY

5002 KRM	1
SENDER	1
CABLE	1
T-LIGHT	1
INSTALLATION KIT	1
APPLICATION SHEET	1

FITTING INFORMATION



INSTALL THE TACHOGRAPH IN A SUITABLE LOCATION, SEE DVSA FITMENT GUIDE ON PAGE 3.

T-LIGHT SUPPLIED MUST BE FITTED AS PER DVSA REQUIREMENTS IF THE VU IS INSTALLED IN A DVSA DESIGNATED AMBER LOCATION.

REMOVE BLANKING PLUG AND INSTALL THE (9954-257) GEARBOX SENSOR , LOCATION IS PICTURED LEFT.

ROUTE AND SECURE THE SUPPLIED SENSOR CABLE TO THE VU LOCATION POINT THROUGH THE BUNG IN THE FOOTWELL UNDERNEATH THE NEARSIDE CARPET.



LOCATE SUITABLE POWER AND GROUND CONNECTIONS AND ROUTE TO THE VU LOCATION POINT, ENSURE THAT THE PERMENANT 12V SUPPLY TO VU PIN A1 IS TERMINATED THROUGH 1 AMP FUSE.

SECOND SOURCE IMS USES TACHO-MOTION SUPPLIED IN THIS KIT SETTING INSTRUCTIONS ARE ON PAGE 2 OF THIS APPLICATION SHEET.

Workshop Technical Support

Tel +44 (0) 1382 866 700

Fax +44 (0) 1382 866 401

Email workshop.support@stoneridge.com

Sales Office

Tel +44 (0) 1382 866 400 (choose opt.1)

Fax +44 (0) 1382 866 401

Email sales@stoneridge.com



Whilst we have endeavoured to ensure the accuracy of the information supplied, Stoneridge Electronics cannot be held responsible for any errors or omissions. It is the installer's responsibility to ensure compliance with specific vehicle manufacturers repair procedures, especially with regard to the procedure for disconnection/reconnection of the battery. Failure to comply with the vehicle manufacturers instructions may result in personal injury and/or component damage/data loss.

DIGITAL APPLICATION SHEET



1. The 2nd Source of motion is obtained by using the GPS Module and cable harness, as shown above.



2. The cable harness is connected directly in line with the tachograph power cable when connecting to the tachograph as shown.



3. The GPS Module should be placed in a suitable position within the cab, preferably in an area next to the windscreen.

C3-Factor	Minimum L	Maximum L
13	1563	1688
14	1688	1813
15	1813	1938
16	1938	2063
17	2063	2188
18	2188	2313
19	2313	2438
20	2438	2563
21	2563	2688
22	2688	2813
23	2813	2938
24	2938	3063
25	3063	3188
26	3188	3313
27	3313	3438
28	3438	3563

4. Set the IMS input to C3 enable in MKIII Programmer, Sensor Settings and set the Speed Factor to correct C3 Factor value using the L factor table above.

Workshop Technical Support

Tel +44 (0) 1382 866 700

Fax +44 (0) 1382 866 401

Email workshop.support@stoneridge.com

Sales Office

Tel +44 (0) 1382 866 400 (choose opt.1)

Fax +44 (0) 1382 866 401

Email sales@stoneridge.com



Whilst we have endeavoured to ensure the accuracy of the information supplied, Stoneridge Electronics cannot be held responsible for any errors or omissions. It is the installer's responsibility to ensure compliance with specific vehicle manufacturers repair procedures, especially with regard to the procedure for disconnection/reconnection of the battery. Failure to comply with the vehicle manufacturers instructions may result in personal injury and/or component damage/data loss.

DIGITAL APPLICATION SHEET



Stoneridge T-light kit 7800-217.



The red lead is connected to the D3 pin of the VU which is a +Ve supply and the black lead is connected to the D4 pin of the VU which is a general warning output. Both are connected via a brown mini-timer plug. (not supplied)

For the T-light to operate correctly, the VU pin D4 Pin function must be set to 'DTC Active'-Enable. This can be done using either the Stoneridge Optimo tool or the MKII programmer.

With the D4 set correctly the T-light will switch on when the VU detects DTC's

Once the T-light warning has been acknowledged by pressing the OK button, the T-light will remain ON for around 1 minute before switching OFF.


VU FITMENT LOCATION

Important:

The recording equipment must be positioned in the vehicle so that it does not:

- obscure the driver's view of the road
- impede the movement of anyone in the vehicle
- interfere or obstruct safety systems within the vehicle (i.e. airbag operation)
- increase the likelihood of injury to anyone in the vehicle

Fitment under the driver's or passenger's seat is never acceptable



DVSA considers that the **amber** area is acceptable if the visual T-light is situated in the driver's field of vision both by day and by night.

DVSA considers that fitting a VU in any of the **green** areas is acceptable.

The **blue** area is acceptable if the location does not obscure the driver's view of the road.

Workshop Technical Support

Tel +44 (0) 1382 866 700

Fax +44 (0) 1382 866 401

Email workshop.support@stoneridge.com

Sales Office

Tel +44 (0) 1382 866 400 (choose opt.1)

Fax +44 (0) 1382 866 401

Email sales@stoneridge.com



Whilst we have endeavoured to ensure the accuracy of the information supplied, Stoneridge Electronics cannot be held responsible for any errors or omissions. It is the installer's responsibility to ensure compliance with specific vehicle manufacturers repair procedures, especially with regard to the procedure for disconnection/reconnection of the battery. Failure to comply with the vehicle manufacturers instructions may result in personal injury and/or component damage/data loss.